

above-referenced Patent Application as following:

AMENDMENT

IN THE CLAIM

Please cancel Claims 1 and 2, without prejudice or disclaimer of the subject matter thereof, and add a claim 3 as the following, the new claim 3 is amended from the previous presented claim 2 so that the claim 3 present the object illustrated in Fig. 5 of the specification. Thereby, it is assured that the amendment of claim 3 is based on the original claim and thus no new matter is added. A details of the claims 3 is illustrated in the following remark which makes the Examiner can understand the claim 3 easily.

LIST OF CLAIMS:

Claims 1 - 2 (Cancelled)

Claim 3. (New) A cable lock comprising:

a body having a key hole in a lower side, a fix hole and an insert hole spaced apart in an upper side, and a pin hole in a vertical side communicating with the fix hole for a fix pin to fit firmly therein; the fix hole and the insert hole are at the side of the body;

a cable combined with the body, having good flexibility to freely bend, and a tubular cover fits around and protects the cable, made up with plural metal rings continually connected with one another; each ring having one end formed with a round projection and the other end formed with a curved recess, so the round projection of one ring is engaged with the curved recess of another ring located next to each other so as to make up the tubular cover; thus the tubular cover is flexible to bend freely together with the cable;

a fix bolt attached with one end of the cable, and then fixed firmly in the

insert hole, having a hole for receiving the cable to fit firmly therein, and one end of the fixing bolt being formed with a curved recess for receiving the round projection of the ring and an outer middle section of the fix bolt being formed with an annular groove which has a flat annular bottom;

a removable bolt attached with the other end of the cable, and inserted in or pulled out of the insert hole of the body, having a hole on an upper end for receiving one end of the cable to fit firmly therein, and a round projection for receiving a lower end of the curved recess and an outer middle section of the removable bolt further having an annular groove which has a flat annular bottom and two sides of annular groove have an equal diameter;

wherein in assembling, the metal rings are continually connected with one another around the cable, with the round projections of one ring engaging with the curved recess of a neighboring ring; then insert one end of the cable firmly in the hole of the fix bolt, and subsequently press sidewise the fix bolt to sandwich tightly the end of the cable therein; next, insert the other end of the cable in the hole of the removable bolt, and press sidewise the removable bolt to sandwich tightly the other end of the cable therein; thus, the tubular cover and the fix bolt and the removable bolt are secured with the cable; then the fix bolt is inserted in the fix hole and insert the fix pin in the lock hole, with the inner end of the fix pin fitting in the annular groove of the fix bolt so that the fix bolt may be secured in the body; thus the cable lock is finished in its assembly.